

Safety Regulations Diam 24

All Diam 24 boats will be equipped with the following safety items:

ANNEXE 5 : KIT DE MOUILLAGE

- A.5.1 Le kit de mouillage est fourni par ADH Inotec.
A.5.2 En course, il est obligatoirement présent à bord, dans le coffre arrière de la coque centrale
A.5.3 Composition :
1 baïlle de mouillage,
1 ancre plate de 8 kg. (Longueur 650mm x largeur 320 mm),
4.3 Mètres de chaîne de 8 mm (6 kg),
22 mètres de bout diamètre 8 mm, Cousin Equinox, polyester.



ANNEXE 6 : KIT MATERIEL DE SECURITE ET KIT D'ASSECHEMENT

- A.6.1 Le kit de sécurité et le kit d'assèchement sont fournis par ADH Inotec.
A.6.2 En course, ils sont obligatoirement présents à bord.
A.6.3 Composition kit sécurité
1 Sac étanche,
1 flash light par équipier embarqué,
3 feux rouges à main,
3 feux de navigation,
1 compas,
1 lampe étanche,
1 miroir de signalisation,
1 pochette contenant les 3 pavillons réglementaires,
1 corne de brume,
1 VHF flottante étanche,
1 couteau
A6.4 2 pagaies fournies par ADH à mettre dans le coffre avant de la coque centrale
Composition Kit Assèchement
1 écope,
1 pompe à main



ANNEXE 7 : DESCRIPTIF MOTEUR

Le moteur est de marque Torqeedo modèle 1003 configuration spécifique développée pour chantier ADH inotec.
Il est constitué : D'un Pylon équipé d'une hélice, 1 Batterie, 1 Remote, câble alimentation, câble de commande, clé magnétique.
Le pylon est monté sur une chaise en inox par ADH inotec



APPENDIX 5: MOORING KIT

- A.5.1 Mooring kit is provided by ADH INOTEC.
A.5.2 When racing, it shall be on board, in the locker of the central hull.
A.5.3 Composition:
- 1 anchor locker,
- 1 flat anchor (8kg) (Length 650mm x Width 320mm),
- 4.3m of chain 8mm (6kg),
- 22m diameter 8mm, Equinox COUSIN, polyester rope.



APPENDIX 6: SAFETY EQUIPMENT KIT AND DRYING KIT

- A.6.1 The safety kit is provided by ADH INOTEC.
A.6.2 When racing, it shall be on board.
A.6.3 Items in the safety kit:
- 1 waterproof bag,
- 1 flashlight per crewmember on board,
- 3 red hand flares,
- 3 portable navigation lights,
- 1 compass,
- 1 waterproof light,
- 1 mirror,
- 1 bag containing 3 regulatory flags,
- 1 foghorn,
- 1 waterproof floating VHF,
- 1 knife
- 2 paddles provided by ADH to be placed in the central hull front locker.
A.6.4 Items in the drying kit:
- 1 scoop,
- 1 hand pump.



APPENDIX 7: ENGINE

The motor is a Torqeedo model 1003 specific configuration developed for ADH inotec site. It is composed of : Trolling motor: 1 shaft fitted with 1 propeller, 1 battery, 1 remote control, 1 power cable, 1 Control cable, 1 magnetic key.
The trolling motor is mounted on a stainless steel bracket supplied by ADH INOTEC



Plus:

Redress KIT on each boat

Charged cell phone with data plan.

VHF handle to be always held by one crew member.

Safety boat on standby.

Diam class to provide and arrange driver for safety boat.

Without safety boat on standby, the Diam 24 fleet, will not be started by the Race Committee.

In case of a emergency / capsize / damage on mats or hull, all Diam 24 competitors stop racing, regroup at damaged boat and communicate with Safety boat.

As described in the Standard Sailing Instructions for Keelboat and Multihull Club Racing:

13. DISCLAIMER OF LIABILITY

13.1 Competitors participate entirely at their own risk. The organizing authority will not accept any liability for material damage or personal injury or death sustained in conjunction with or prior to, during, or after the regatta.